



food



agriculture



transport



consumer



TOPCAT



TOPCAT

- Three ceramic coated pistons brass axial pump head with built-in by-pass valve.
- Automatic Stop System
- DSP: Direct Shut down Protection
- Detergent built-in tank for indirect suction.
- Power cable (5 m).
- Pressure regulator.
- Glycerine pressure gauge.



	TOPCAT 9-130 ECO	TOPCAT 12-100	TOPCAT 9-140
Code	2453	2451	2452
operat. pressure	130 bar	100 bar	140 bar
operat. pressure	1911 psi	1470 psi	2058 psi
delivery rate	9 l/min	12 l/min	9 l/min
abs. power/voltage	2800W- 240V~50Hz (Ph1)	2800W- 240V~50Hz (Ph1)	2800W- 240V~50Hz (Ph1)
RPM	2800	1450	1450
detergent tank	4 l/ 1.05 gal	4 l/ 1.05 gal	4 l/ 1.05 gal
inlet max temperature	40° C	40° C	40° C
machine dimensions	59x37x87	59x37x87	59x37x87
machine weight	28 Kg / 61,6 lbs	35 Kg / 77 lbs	35 Kg / 77 lbs
Hose-reel	INCLUDED	OPTIONAL	OPTIONAL