




food



agriculture



transport



hire



public sectors



industry



MANX



MANX

- 4 pole electrical motor (1450 RPM) with thermal protection, water cooling and elastic joint.
- Three ceramic pistons, brass linear.
- Pump head with separate by-pass valve.
- Suction and Delivery S/S valves.
- LSP: Late Shut down Protection 24 V
- Integrated detergent suction with external suction probe
- Power cable (5 m)
- Pressure regulator
- Glycerine pressure gauge.
- Tough steel main frame.

Optional:

- Hose-reel code 6.608.0017

	MANX 12-100	MANX 11-100	MANX 15-150	MANX 21-200
Code	2470	2471	2472	2473
operat. pressure	100 bar	100 bar	150 bar	200 bar
operat. pressure	1470 psi	1470 psi	2205 psi	2940 psi
delivery rate	12 l/min	11 l/min	15 l/min	21 l/min
abs. power/voltage	2800W- 240V~50Hz (Ph1)	2800W- 110V~50Hz (Ph1)	5000W- 415V~50Hz (Ph3)	9400W- 415V~50Hz (Ph3)
RPM	1450	1450	1450	1450
detergent tank	-	-	-	-
inlet max temperature	40° C	40° C	40° C	40° C
machine dimensions	50x90x83	50x90x83	50x90x83	50x90x83
machine weight	44 Kg / 96.8 lbs	44 Kg / 96.8 lbs	44 Kg / 96.8 lbs	52,5 Kg / 115.5 lbs