



food



agriculture



transport



hire



public sectors



industry

EDGE



EDGEVAC53P / EDGEVAC53S

EDGEVAC53P / EDGEVAC53S

- Silenced two stages motor.
- Professional closing hooks
- Suction system with bypass cooling.
- Plastic tank (PP) (EDGEVAC53P)
- S/S tank (EDGEVAC53S)
- Power cable 10 mt
- Drain hose system
- Shock proof trolley
- Easy standing head (during filter cleaning)
- Liquid float valve
- Optional Plug for electric tools (max 1800 W)
- Static electric shock inhibitor (EDGEVAC53S)



Wet & Dry Vacuum cleaners

Standard accessories:

- Ø40 flexible hose (m2,5)
- Chromium-plated steel curve
- Chromium-plated steel extension pipes (2 pcs)
- Flat lance • Round brush • Holder for floor accessories
- Bristle brush • Liquid tool • Complete filter

	EDGEVAC53P	EDGEVAC53S
Code	7405	7406
Voltage	220-240V~ 50-60Hz	220-240V~ 50-60Hz
N° / motor type	1x/silenced two stage motor	1x/silenced two stage motor
power (max)	1200 (1400) W	1200 (1400) W
motor cooling	by-pass	by-pass
column depression	21,6 kPa/ 2200 mm H2O	21,6 kPa/ 2200 mm H2O
air suction	53 l/s	53 l/s
total volume / dust /liquid	50l. / 21l. /35l.	50l. / 21l. /35l.
motor protection	floating valve	floating valve
emptying system	hose Ø 28 mm	hose Ø 28 mm
electrical cable lenght	10 m	10 m
dimensions/ machine weight	62x51x85 cm/ 15 Kg	62x51x85 cm/ 16,5 Kg