


**EDGE**

food



agriculture



transport



hire



public sectors



industry



EDGEVAC78P

EDGEVAC78P

- 2 Silenced two stage Motor
- Professional closing hooks
- Suction system with by-pass cooling.
- Plastic tank (PP)
- Liquid float valve
- 10 m power cable
- Shock proof trolley
- Ergonomic handle tank, head and trolley
- Easy standing head (during filter cleaning)
- Drain hose system

Standard accessories:

- Ø40 flexible hose (m2,5)
- Chromium-plated steel curve
- Chromium-plated steel extension pipe
- Flat lance
- Round brush
- Holder for floor accessories
- Bristle brush
- Liquid brush
- Complete filter



EDGEVAC78P2T/ EDGEVAC78P3T

EDGEVAC78P/EDGEVAC78P3T

- 2 Silenced two stage Motor (EDGEVAC78P/EDGEVAC78P2T)
- 3 Silenced two stage Motor (EDGEVAC78P3T)
- Professional closing hooks
- Suction system with by-pass cooling
- Plastic tank (PP)
- Tilting tank
- Fully removable tank
- Liquid float valve
- 10 m power cable
- Cable holder
- Ergonomic handle tank, head and trolley
- Easy standing head (during filter cleaning)

Standard accessories:

- Ø40 flexible hose (m2,5)
- Chromium-plated steel curve
- Chromium-plated steel extension pipe
- Flat lance
- Round brush
- Holder for floor accessories
- Bristle brush
- Liquid brush
- Complete filter

	EDGEVAC78P	EDGEVAC78P2T	EDGEVAC78P3T
Code	7407	7408	7409
Voltage	220-240V~ 50-60Hz	220-240V~ 50-60Hz	220-240V~ 50-60Hz
N° / motor type	2x/silenced two stage motor	2x/silenced two stage motor	3x/silenced two stage motor
power (max)	2000 (2400) W	2000 (2400) W	3000 (3600) W
motor cooling	by-pass	by-pass	by-pass
column depression	22 kPa/ 2240 mm H2O	22 kPa/ 2240 mm H2O	22 kPa/ 2240 mm H2O
air suction	108 l/s	108 l/s	162 l/s
total volume / dust /liquid	77 l. / 34 l. /47 l.	77 l. / 34 l. /47 l.	77 l. / 34 l. /47 l.
motor protection	floating valve	floating valve	floating valve
emptying system	hose Ø 28 mm	tilting tank	tilting tank
electrical cable lenght	10 m	10 m	10 m
dimensions/ machine weight	62x51x96 cm/ 21 Kg	62x51x99 cm/ 24 Kg	62x51x99 cm/ 25 Kg