



food



agriculture



transport



hire



public sectors



industry

EDGE



EDGEVAC78S2/ EDGEVAC78S3

EDGEVAC78S2/EDGEVAC78S3

- 2 Silenced two stage Motor (EDGEVAC78S2) • 3 Silenced two stage Motor (EDGEVAC78S3) • Professional closing hooks
- Suction system with by-pass cooling • S/S tank • Liquid float valve • 10 m power cable • Static electric shock inhibitor • Shock proof trolley • Ergonomic handle tank, head and trolley
- Easy standing head (during filter cleaning)

Standard accessories:

- Ø40 flexible hose (m2,5) • Chromium-plated steel curve
- Chromium-plated steel extension pipes
- Flat lance • Round brush
- Holder for floor accessories
- Bristle brush
- Liquid brush • Complete filter

EDGEVAC78S2T / EDGEVAC78S3T

EDGEVAC78S2T/ EDGEVAC78S3T

- 2 Silenced two stage Motor (EDGEVAC78S2T) • 3 Silenced two stage Motor (EDGEVAC78S3T) • Professional closing hooks • Suction system with by-pass cooling • S/S tank • Tilting tank • Fully removable tank • Plastic handle • Liquid float valve • 10 m power cable • Cable holder
- Ergonomic handle tank, head and trolley • Shock proof trolley • Easy standing head (during filter cleaning) • Static electric shock inhibitor

Standard accessories:

- Ø40 flexible hose (m2,5) • Chromium-plated steel curve • Chromium-plated steel extension pipe • Flat lance • Round brush • Holder for floor accessories • Bristle brush • Liquid brush • Complete filter



VACUUMS

	EDGEVAC78S2	EDGEVAC78S3	EDGEVAC78S2T	EDGEVAC78S3T
Code	7410	7411	7412	7413
Voltage	220-240V~ 50-60Hz	220-240V~ 50-60Hz	220-240V~ 50-60Hz	220-240V~ 50-60Hz
N° / motor type	2x/silenced two stage motor	3x/silenced two stage motor	2x/silenced two stage motor	3x/silenced two stage motor
power (max)	2000 (2400) W	3000 (3600) W	2000 (2400) W	3000 (3600) W
motor cooling	by-pass	by-pass	by-pass	by-pass
column depression	22 kPa/ 2240 mm H2O	22 kPa/ 2240 mm H2O	22 kPa/ 2240 mm H2O	22 kPa/ 2240 mm H2O
air suction	108 l/s	162 l/s	108 l/s	162 l/s
total volume / dust /liquid	78 l. / 35 l. /48 l.	78 l. / 35 l. /48 l.	78 l. / 35 l. /48 l.	78 l. / 35 l. /48 l.
motor protection	floating valve	floating valve	floating valve	floating valve
emptying system	hose Ø 28 mm	tilting tank	tilting tank	tilting tank
electrical cable length	10 m	10 m	10 m	10 m
dimensions/ machine weight	62x51x96 cm/ 23 Kg	62x51x99 cm/ 27 Kg	62x51x99 cm/ 26 Kg	62x51x99 cm/ 27 Kg