


**EDGE**

food



agriculture



transport



hire



public sectors



industry

EDGEEXTVAC53 / EDGEEXTVAC78 / EDGEEXTVAC78T**EDGEEXTVAC53**

- 1 Two stage silenced motor
- Professional closing hook
- Suction system with bypass coolings
- S/S tank
- Detergent pump (Motor 32W - 0,8 l/min)
- Easy standing head (during filter cleaning)
- Static electric shock inhibitor

Standard accessories:

- Ø40 flexible hose mt 2,5
- complete carpet accessory
- Fabric filter
- Arm-chair nozzle

EDGEEXTVAC78 / EDGEEXTVAC78T

- 2 Silenced two stage motor
- Professional closing hooks
- Fully removable tank (EDGEEXTVAC78T)
- Suction system with bypass cooling
- S/S tank
- Detergent pump (Motor 48W - 1,2 l/min)
- Tilting tank (EDGEEXTVAC78T)
- Drain hose system (EDGEEXTVAC78)
- Cable holder
- Ergonomic handle tank, head and trolley
- Easy standing head (during filter cleaning)
- Static electric shock inhibitor
- External detergent tank

Standard equipment:

- Ø40 flexible hose mt 2,5
- complete carpet accessory
- Fabric filter
- Arm-chair nozzle

	EDGEEXTVAC53	EDGEEXTVAC78	EDGEEXTVAC78T
Code	7414	7415	7416
Voltage	230V~ 50Hz / 10 m	230V~ 50Hz / 10 m	230V~ 50Hz / 10 m
N° / motor type	1x/silenced two stage motor	2x/silenced two stage motor	2x/silenced two stage motor
power (max)	1200 (1400) W	2200 (2400) W	2200 (2400) W
column depression	21,6 kPa/ 2200 mm H2O	22 kPa/ 2240 mm H2O	22 kPa/ 2240 mm H2O
air suction	53 l/s	108 l/s	108 l/s
total volume / dust /liquid	50 l. / 21 l. / 35 l.	78 l. / 35 l. / 48 l.	78 l. / 35 l. / 48 l.
detergent pump	1x32W - 0,8 l/min	2x48W - 0,7-1,2 l/min	2x48W - 0,7-1,2 l/min
detergent pump pressure	3,5 bar	5 bar	5 bar
detergent tank	11 l.	25 l.	11 l.
emptying system	hose Ø 28 mm	hose Ø 28 mm	tilting tank
dimensions/ machine weight	62x51x85 cm/ 19 Kg	62x51x96 cm/ 29,5 Kg	62x51x99 cm/ 29,5 Kg