




food



agriculture



transport



hire



public sectors



consumer



industry

EDGE



A12

- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch.
- Large handle with traction driving lever for forward and backward directions.
- Self levelling brush plate
- Cover removable without tools.
- Vacuum motor and filter inspection, quickly and without tools.
- Detergent solution tank provided with large opening protected by quick locking cap.

A12



scrubber driers

	A12 66T	A12 75T
Code	6311	6312
Power supply	24V	24V
scrubbing / squeegee width	660 / 900 mm	750 / 900 mm
max speed/working capacity	5,7 km/h -3762 m ² /h	5,7 km/h -4275 m ² /h
detergent tank capacity	88 l / 23,25 gal	88 l / 23,25 gal
recovery tank capacity	91-95 l/24,04-25 gal	91-95 l/24,04-25 gal
traction motor	automatic / 300W	automatic / 300W
RPM/ pressure on the brushes	150-43,5 kg /95,9 lbs	150-43,5 kg /95,9 lbs
brush motor power	1000W	1000W
detergent solution system	mech./ solenoide valve	mech./ solenoide valve
depression/ vacuum motor	1733 mmH ₂ O/ 550W	1733 mmH ₂ O/ 550W
dimensions / weight	133x73x117cm/ 153kg	133x80x117cm/ 153kg

