



food



transport



hire



public sectors



industry



A18-R



A18-R

- More than 60/80 Kg. of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size • Stability even when fully loaded • Front independent wheel-drive with tight steering radius • Easy access to electrical components • Detergent dispenser
- Automatic device for squeegee lifting while reversing • Automatic device that stops brushes and detergent supply when the machine is standing still
- Antifoam device
- Self-levelling brushes
- High-performance batteries resulting in high-working efficiency

• no. of battery and max. capacity (optional): 1x24V/525Ah C5 1200 cycles (cassone)

	A18-R 4600	A18-R 5700
Code	6401	6402
Power supply	24V	24V
scrubbing / squeegee width	660 / 900 mm	820 / 1000 mm
max speed/working capacity	7 km/h - 4620 m ² /h	7 km/h - 5740 m ² /h
detergent tank capacity	140 l / 36,99 gal	140 l / 36,99 gal
recovery tank capacity	150-180 l/39,6-47,6 gal	150-180 l/39,6-47,6 gal
traction motor	front wheel / 900W	front wheel / 900W
RPM/ pressure on the brushes	150-60 kg /132 lbs	150-80 kg /176 lbs
brush motor power	1000W	1000W
max gradient empty / full tank	10 / 7%	10 / 7%
depression/ vacuum motor	1734 mmH ₂ O/ 550W	1734 mmH ₂ O/ 550W
dimensions / weight	175x77x149cm/ 238kg	175x93x149cm/ 258kg



scrubber driers