




food



agriculture



transport



hire



public sectors



industry



S 2600 SC/ S 3400 SC

S 2600 SC / S 3400 SC

- Gasoline motor Honda 4 HP/2,9 kW • Max. possible gradient 20% • Max operating speed 4km/h • Hourly efficiency (max) 2600 m²/h (S 2600 SC) • Hourly efficiency (max) 3400 m²/h (S 3400 SC) • Working area (1 side brush) 655 mm (S 2600 SC) • Working area (1 side brush) 850 mm (S 3400 SC) • Mechanically operated main controls. • Wide panel filter with manual filter shaker. • Long life elastic belts. • Suction selection drive. • Side brush raising control. • Main brush pressure regulation. • Wide collection tank.

S 2200 BT/ S 3400 BT

S 2200 BT / S 3400 BT

- Electric motor 12V/250W (S 2200 BT); 12V/400W (S 3400 BT)
- Max possible gradient 18-20% • Max operating speed 4km/h
- No. of batteries and max capacity:
1x12V 80 Ah (C 20) (S 2200 BT);
1x12V 157 Ah (C 20) (S 3400 BT);
2x 6V 240 Ah (C 20)(S 3400 BT)
- Hourly efficiency (max) 2600 m²/h (S 2200 BT)
- Hourly efficiency (max) 3400 m²/h (S 3400 BT)
- Working area 655 mm (S 2200 BT) • Working area
- Mechanically operated main controls.
- Wide panel filter with manual filter shaker. • Long life elastic belts.
- Suction selection drive. • Side brush raising control. • Main brush pressure regulation. • Wide collection tank.



	S 2600 SC	S 3400 SC	S 2200 BT	S 3400 BT
Code	5116	5117	5118	5119
main brush width	510mm/ 20,08inc	700mm/ 27,56inc	510mm/ 20,08inc	700mm/ 27,56inc
main brush + 1 side brush width	655mm / 25,79inc	850mm / 33,46inc	655mm / 25,79inc	850mm / 33,46inc
collector tank	40lt-10,57gal	60lt-15,85gal	40lt-10,57gal	60lt/15,85gal
max working capacity	2620 m ² /h - 28201 ft ²	3400 m ² /h - 36597 ft ²	2620 m ² /h - 28201 ft ²	3400 m ² /h - 36597 ft ²
traction/ limiting gradient	mechanical / max 20%	mechanical / max 20%	mechanical / max 18%	mechanical / max 20%
max speed	4 km/ h- 2,49 mile/h	4 km/ h- 2,49 mile/h	4 km/ h- 2,49 mile/h	4 km/h - 2,49 mile/h
motor type / power	Honda 4 HP / 2,9 Kw	Honda 4 HP /2,9kW	12V / 250W	12V / 400W
filtering surface	2 m ² / 21,53 ftp ²	3,2 m ² / 32,50 ftp ²	2 m ² /21,53 ft ²	3,02 m ² /32,50 ft ²
pressure on the brushes	regulable	regulable	regulable	regulable
RPM main brush / side brush	300/90	300/90	300 / 90	300 / 90
dimension / weight	129x63x97/ 562kg	138x79x98/ 110kg	129x63x97/ 53kg	138x79x98/ 81kg