

**EDGE**

food



transport



hire



public sectors



industry

S 6800 SC / S 6800 BT



S 6800 SC/S 6800 BT

- Shock-proof steel frame. • Perfectly balanced weight of the components, thus resulting in totally safe quick changes of direction. • Wide collection compartment. • Large filtering surface distributed on 4 cartridge filters fitted with electronic filter-shaker. • Easy-to-use machine drives. • Easy and quick routine maintenance. • On request, additional side brush / dust-laying front system.

S 6800 SC

- gasoline engine Honda 5 HP/3,7 kW
- limiting gradient 15% • hydraulic rear drive • max.working speed 5.8 Km/h • hourly efficiency : 6800 m²/h
- working width: 950 mm (max 1250 mm)

S 6800 BT

- electric motor 24V/990W • limiting gradient 16%
- hydraulic rear drive • max.working speed 5.8 Km/h
- hourly efficiency : 6800 m²/h • working width: 950 mm (max 1250 mm)

	S 6800 BT	S 6800 SC
Code	6150	6151
main brush width	700mm/ 27,56inc	700mm/ 27,56inc
main brush + 1 side brush	950mm / 37,40inc	950mm / 37,40inc
main brush + 2 side brushes	1250mm/ 49,21inc	1250mm/ 49,21inc
collector tank	85lt - 22,46gal	85lt - 22,46gal
max working capacity	7250 m ² /h - 78038 ft ²	7250 m ² /h - 78038 ft ²
traction/ limiting gradient	rear wheels / 16%	front wheel / 15%
max speed	5,8 km/ h- 3,60 mile/h	5,8 km/ h- 3,60 mile/h
motor type / power	24V / 990W	Honda 5 HP / 3,7kW
filtering surface	4 m ² / 43,06 ftp ²	4 m ² / 43,06 ftp ²
filter shaker	electric	electric
dimension / weight	123x98x127 cm/ 184kg	123x98x127 cm/ 230kg
dimension / weight	129x63x97/ 53kg	129x63x97/ 62kg